

# CANDY PROCESS EQUIPMENT

## SLAB CLOTH




### NON-STICK FOOD GRADE CLOTH FOR COVERING WORK SURFACES

Food grade non-stick material suitable for covering your work benches or slabs.

The material is ideal for working with candy and other confectionery products.

The material is easy to clean and wipe down after use.

### FEATURES

-  100% food grade certified
-  Strong and durable
-  Easy to clean



PRODUCT CONSTRUCTION		TECHNICAL DATA	
Number of fabrics	2	Thickness	1.4 mm 0.055 inch
Fabric toplayer	RFLA, frayless	Weight	1.6 kg/m <sup>2</sup> 0.32 lb/ft <sup>2</sup>
Fabric bottomlayer	RFLA, frayless	Coefficient of friction bottomside on steel	0.25
Thickness cover	0.2 mm 0.008 inch	Tensile force for 1% strain	10.0 N/mm 57.1 lbf/in.
Material topside	SPU	Recommended tension: strain	0.4-0.7 %
Hardness toplayer	86 shore A	Recommended tension	4.0-7.0 N/mm 23-40 lbf/in.
Color	white 1	Maximum strain	1.20%
Profile topside	satın mat finish (m)	Maximum tension	13.0 N/mm 74.2 lbf/in.
Thickness bottomside	0.1 mm 0.004 inch		
Material bottomside	fabric, impregnated PU		
PULLEY		PROPERTIES	
Minimum pulley diameter normal flexing 180°	20 mm 0.79 inch	Oil and grease resistant	Yes
Minimum pulley diameter back flexing 180°	40 mm 1.57 inch	Temperature range	-40 - 100 °C -40 - 212 °F
Carrying rollers	Yes	Antistatic fabric	Yes
Slider bed	Yes	Antistatic cover	No
Troughed installation	No	Flame retardant	No
INTERNATIONAL STANDARDS		Lateral stabil	Yes
EU food contact	Yes <sup>1</sup>	Frayless	Yes
FDA food contact	Yes <sup>1</sup>		
<sup>1</sup> For more detailed information regarding food contact, please request a statement			