

## HAND FED DOUBLE TWIST WRAPPER-CHAIN INFEED- TW05

### THE VERSATILE SOLUTION FOR FEEDING AND WRAPPING IN DOUBLE TWIST STYLE.

The hand-feed double twist wrapping machine is capable of wrapping in excess of 100 pieces per minute, depending on the product's shape and size. The machine is capable of running much faster, but this is the speed 2 operators can typically handle.

Its self-contained lubrication system ensures smooth operation, while Lexan clear guards provide high visibility and are electrically interlocked with magnetic safety switches. The machine automatically stops if the guarding is opened during operation, enhancing operator safety.

The twist wrapper uses a pusher infeed system where products are placed in front of pushers moving along a track, transferring them into the wrapping section. With one operator, the machine can achieve wrapping speeds of 40-70 wraps per minute, and with two operators speeds of over 100 per minute are possible.

Suitable for a wide range of products, including hard candies, jellies, fudges, caramels, nougats, moulded and enrobed chocolates, and more.



### FEATURES

- Wrapping Speed: Up to 100+ wraps per minute, depending on product size and shape.
- Adjustable Film Length: Controlled by keypad and stepper motor. Allowing for quick adjustments
- Safety Guards: Lexan clear guards with magnetic safety switches for automatic stop if opened.
- Pusher Infeed System: Efficiently feeds products into the wrapping section.
- "No Product, No Film" Sensor: Reduces film waste by detecting product presence.
- Versatile Wrapping: Wraps various shapes (balls, rounds, ovals, etc.) and product types (hard candy, fudge, jellies).

## HAND FED DOUBLE TWIST WRAPPER-CHAIN INFEED- TW05

### SPECIFICATIONS

**Overall Height**  
1658mm

**Overall Length**  
3200mm

**Overall Width**  
1650mm

**Material**  
Powder Coated Steel  
Stainless Steel-contact parts

**Product Size Range:**  
Length 12-34mm  
Width 12-34mm  
Depth 6-20mm

**Power**  
3 Phase -3.5kW

**Weight**  
1500Kg

